

Safety Data Sheet (Complies with OSHA HCS)

Section 1: Identification

Trade Name: DX-4400
Contact Information: Dynesic Technologies, Inc.
15230 Surveyor Blvd., Addison, TX 75001
Phone: 972-692-0962
Emergency Contact: Same as Above
Recommended Use: UV-stabilized, non-porous concrete coating/primer for concrete
and other surface prep/coating applications
Chemical Family: 2-Part Clear Epoxy

Section 2: Hazard(s) Identification

Hazard Classification: Skin Irritant- Category 2
Signal Word: Warning
Hazard Statement(s): H317 Prolonged exposure may cause an allergic skin reaction.

Pictogram:



Precautionary Statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children .
P103: Read label before use.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P280: Wear Protective gloves/protective clothing/eye and face protection.
P333+P313: If skin irritation/rash occurs, get medical attention.
P501: Dispose of contents/container in accordance with local/regional/national and international regulations.

NFPA Rating:

Health:	1
Flammability:	1
Instability:	0
Specific Hazard:	N/A

HIMS ® Rating:

Health:	1
Flammability:	1
Physical Hazard:	0
Personal Protection Index:	C

Section 3: Composition/Information on Ingredients

Chemical Name/Family: Epoxy

Common Names/Synonyms: Epoxy Resin, Epoxy Coating, Novolac Epoxy, Two--part Epoxy

CAS Numbers and other Identifiers:

Resin: DGEBA-Epoxy Resin: CAS# 25068-38-6 80%-90%
Trade Secret: 10%-20%

Hardener: Modified Cycloaliphatic Amine: CAS# Mixture >90%
Trade Secret <10%

Trade Secret Claim: Please note that the exact concentration of each chemical contained in the product has been withheld as the exact formula needs to remain a trade secret.

Section 4: First Aid Measures

Description of first--aid measures for specific exposure:

For Ingestion: Resin - If large amounts are ingested, induce vomiting if conscious.
Hardener - Call physician immediately. Give generous amounts of water if conscious. **Do not** induce vomiting.

For Skin Exposure: Resin - Promptly wash with mild soap and water.
Hardener - Promptly wash with mild soap and water.

For Inhalation: Resin - Remove to fresh air. Give oxygen if breathing is difficult.
Hardener - Remove to fresh air. Give oxygen if breathing is difficult.

For Eye Exposure: Resin - Immediately flush eyes with water for 15 minutes.
Call physician.
Hardener - Immediately flush eyes with water for 15 minutes.
Call physician.

Description of overexposure symptoms and effects:

Overexposure to this material can cause chemical burns to the skin and eyes and inhalation of vapors can cause severe respiratory irritation. Can cause allergic skin and respiratory reactions. Can have effects on the nervous system evidenced by central nervous system depression, tremors, paralysis, diarrhea and vasodilation. May also cause head ache, nausea and dizziness.

Medical Conditions Aggravated by Exposure:

Allergy, eczema or skin conditions.

Additional Information:

Promptly remove wet contaminated non---imperious clothing, wash before reuse. Destroy contaminated leather and absorbent shoes.

Section 5: Fire-Fighting Measures

Flash Point:	Resin >300oF (149oC)	Hardener >200oF (93oC)
Flash Point Method Used:	Closed cup	
Fire Fighting Extinguishing Media:	Carbon Dioxide, foam, dry chemical	
Fire Fighting Equipment:	Use a self-contained breathing apparatus	
Fire and Explosion Hazards:	Decomposition and combustion products may be toxic.	

Section 6: Accidental Release Measures

Steps to be taken if material is spilled:

Resin	Shovel into closeable container for disposal.
Hardener	Absorb into sand or other absorbent material. Shovel into closeable container and dispose of in professional manner.

Section 7: Handling and Storage

Handling precautions:	Do not get in eyes, on skin or on clothing. Do not breathe vapor, mist or spray. Use only with adequate ventilation. Individuals should wash thoroughly after handling. For industrial use only.
Storage Information:	Keep away from heat, sparks and open flame. Ground and bond metal containers for liquid transfer to avoid static sparks. Store at temperatures between 2oC and 40oC in tightly closed containers in dry area to prevent moisture and carbon dioxide contamination.

Section 8: Exposure Controls/Personal Protection

OSHA PELs:	N/A
ACGIH TLVs:	N/A
Personal Protective Equipment:	Wear protective equipment to prevent exposure and personal contact
Skin Protection:	Impervious gloves
Respiratory Protection:	Organic chemical cartridge respirator if needed in non-vented area
Eye Protection:	Splash---proof chemical goggles
Engineering Controls:	Good general mechanical ventilation and local exhaust

Section 9: Physical and Chemical Properties

Appearance:	Resin: Clear	Hardener: Clear
Odor:	None	Slight ammonia odor
Physical State:	Liquid	Liquid
Solubility in Water (% by weight):	Negligible	Negligible
Melting Point:	<0o F (-18o C)	<0o F (-18o C)
Density:	1.12	1.03
pH:	ca 5	ca 8

Section 10: Stability and Reactivity

Reactivity: Non Reactive

Stability: Stable

Incompatible Materials: Strong acids, oxidizers and bases

Hazardous Decomposition Products:

Resin: Carbon Monoxide, Carbon Dioxide, Phenolics

Hardener: Carbon Monoxide, Carbon Dioxide, Phenolic
Nitrogen Oxides and Compounds

Hazardous Polymerization:

Resin: Will not occur

Hardener: Do not heat in bulk as dangerous decomposition
may occur, liberating toxic fumes.

Section 11: Toxicological Information

Acute Oral Effects (Ingestion): Resin: LD50 (rabbits): 4000 mg/kg

Hardener: LD50 (rabbits): 3000 mg/kg

Sensitization: Can cause skin and respiratory sensitization

Skin Irritation: Irritant

Eye Irritation: Irritant

Section 12: Ecological Information

Additional Information: Amines, in general, may be toxic to aquatic organisms.
Epoxies are only slightly soluble in water.

Aquatic Toxicity: No further relevant information available

Persistence and Degradability: No further relevant information available

Biocumulative Potential: No further relevant information available

Mobility in Soil: No further relevant information available

Section 13: Disposal Considerations

Waste Disposal Method:

Dispose in accordance with international, federal (US), state (US) and local regulations.

Recommendations:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Section 14: Transport Information

DOT, ADR, AND IMDG, IATA: Non-hazardous for transport

Hazard Class under:

DOT, ADR, AND IMDG, IATA: Non-hazardous for transport

Marine Pollutant: No

Notes: Not Regulated under DOT, ADR, AND, IMDG, IATA

Section 15: Regulatory Information

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200(g). This product is considered to be a hazardous chemical under that standard.



Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

Toxic Substances Control Act (TSCA): All ingredients are on the TSCA inventory and are exempt as per 40CFR723.50 Low Volume Exemption (LVE) and Low Environmental Release and Low Human Exposure Exemption (LoREX).

SARA Title III: Section 304 - CERCLA: Not listed.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Sec. 313 (40 CFR 372). This information must be included in all MSDS's that are copied and distributed for this material.

Section 16: Other Information

This SDS was prepared in accordance with the new OSHA HCS requirements that will go into effect for manufacturers of chemicals on June 2015. This SDS replaces all preceding versions of MSDS and complies with all current regulations.

Revision: August 2016—All rights reserved.



15230 Surveyor Blvd., Addison, TX 75001
Phone: 972-692-0962, www.dynesic.com